

ADPSV grejni kabl, dvožilni kabl sa zaštitnim plaštom i zaštitom od UV zračenja pogodan za poluakumulaciono i akumulaciono grejanje poda u stambenim prostorijama (unutrašnje i spoljašnje primene).

Klasa M2. Hladni kraj 1x5 m. Ø 5,0-5,9 mm.



Kablovi na koturu

TIP (Ohm/m)
38.72
14.02
8.96
5.232
3.58
2.568
1.714
1.382
0.926
0.638
0.424
0.31
0.196
0.136

TIP	Pogodnosti	Max. snaga
Grejanje spoljašnjih površina	Da	20 W/m
Zaštita cevi od zaleđivanja	Da	10 W/m
Grejanje cevovoda	Da	10 W/m
Otapanje snega i leda na krovu	Da	20 W/m



ADPSV kabl.
Pakovan na kartonskom koturu.



Grejni kablovi

SNAGA [W]	Tip ADPSV 10 W/m	DUŽINA [m]
120	10120	11.4
200	10200	18.9
250	10250	23.6
320	10320	31.6
400	10400	36.9
450	10450	45.9
550	10550	56.1
600	10600	63.9
750	10750	75.8
950	10950	87.0
1100	101100	114.5
1300	101300	131.3
1700	101700	158.5
2000	102000	194.5

SNAGA [W]	Tip ADPSV 18 W/m	DUŽINA [m]
160	18160	8.5
260	18260	14.5
320	18320	18.5
420	18420	24.0
520	18520	28.4
600	18600	34.4
740	18740	41.8
830	18830	46.1
1000	181000	57.5
1200	181200	68.9
1500	181500	83.2
1700	181700	100.4
2200	182200	122.7
2600	182600	149.6

SNAGA [W]	Tip ADPSV 20 W/m	DUŽINA [m]
160	20160	8.3
270	20270	14.0
340	20340	17.2
450	20450	22.5
540	20540	27.4
640	20640	32.1
780	20780	39.3
870	20870	43.8
1070	201070	53.5
1290	201290	64.4
1580	201580	79.0
1850	201850	92.4
2300	202300	117.3
2750	202750	141.4