

MADPSP grejni kabl, dvožilni kabl sa zaštitnim plaštom i zaštitom od UV zračenja pogodan za grejanje spoljašnjih površina. Klasa M2. Hladni kraj 1x5 m. Ø 6,2-8,9 mm.



30W/m (35W/m) za otapanja snega i leda u olucima. Mora se koristiti kontrolni sistem sa senzorom za temperaturu i padavine da bi se sprečilo uključenje kabla na temperaturama višim od +5 C.

Kablovi na koturu

TIP (Ohm/m)	SNAGA [W]	MADPSP 25 W/m	DUŽINA [m]	SNAGA [W]	MADPSP 30 W/m	DUŽINA [m]
18.00	270	25270	10.9	300	30300	9.8
6.40	450	25450	18.4	500	30500	16.5
2.70	700	25700	28.0	760	30760	25.8
2.00	800	25800	33.1	880	30880	30.1
1.20	1050	251050	42.0	1150	301150	38.3
0.72	1350	251250	54.4	1500	301500	49.0
0.60	1480	251480	58.5	1600	301600	54.1
0.36	1900	251900	74.8	2100	302100	67.8
0.25	2300	252300	87.2	2500	302500	80.5
0.18	2700	252700	103.9	3000	303000	93.5
0.08	4000	254000	165.3	4400	304400	150.3
0.04	5700	255700	203.5	6300	306300	183.7

MADPSP kabl, 400 V

SNAGA [W]	MADPSP 20 W/m 400 V	DUŽINA [m]	SNAGA [W]	MADPSP 30 W/m 400 V	DUŽINA [m]
420	20420	20.2	520	30520	17.1
700	20700	35.7	860	30860	29.1
1100	201100	53.9	1330	301330	44.6
1250	201250	64.0	1550	301550	51.6
1600	201600	83.3	2000	302000	66.7
2100	202100	105.8	2600	302600	85.5
2300	202300	113.7	2800	302800	93.4
3000	203000	143.5	3600	303600	119.8
3600	203600	168.7	4500	304500	134.9
4200	204200	202.2	5100	305100	166.7
6300	206300	317.5	7700	307700	259.7

