

MPSV grejni kabl, jednožilni kabl sa zaštitnim plaštom i zaštitom od UV zračenja. Pogodan je za grejanje spoljašnjih površina. Hladni kraj 2x5 m. Ø 5,0-5,5 mm.



30W/m za otapanje snega i leda u olucima. Mora se koristiti kontrolni sistem sa senzorom za temperaturu i padavine da bi se sprečilo uključenje kabla na temperaturama višim od +5°C.

Kablovi na koturu

TIP (Ohm/m)
9.00
6.50
3.20
1.35
1.00
0.60
0.36
0.25
0.183
0.155
0.098
0.068
0.04

Grejni kablovi 230V

SNAGA [W]	Tip MAPSV 20 W/m	DUŽINA [m]
340	20340	17.3
400	20400	20.3
570	20570	29.0
880	20880	44.5
1030	201030	51.4
1350	201350	65.3
1750	201750	84.0
2100	202100	100.8
2400	202400	120.4
2600	202600	131.3
3300	203300	163.6
4000	204000	194.5
5100	205100	259.3

SNAGA [W]	Tip MAPSV 25 W/m	DUŽINA [m]
380	25380	15.5
450	25450	18.1
640	25640	25.8
990	25990	40.0
1150	251150	46.0
1480	251480	59.6
1900	251900	77.3
2300	252300	92.0
2700	252700	107.1
2900	252900	117.1
3700	253700	145.9
4400	254400	176.8
5700	255700	232.0

SNAGA [W]	Tip MAPSV 30 W/m	DUŽINA [m]
420	30420	14.0
500	30500	16.3
700	30700	23.6
1100	301100	35.6
1250	301250	42.3
1600	301600	55.1
2100	302100	70.0
2500	302500	84.6
2950	302950	98.0
3200	303200	106.7
4000	304000	134.9
4800	304800	162.1
6300	306300	209.9

MAPSV kablovi 400 V

SNAGA [W]	Tip MAPSV 20 W/m - 400 V	DUŽINA [m]
600	20600	29.6
700	20700	35.2
1000	201000	50.0
1550	201550	76.5
1800	201800	88.9
2300	202300	115.9
3000	203000	148.1
3500	203500	182.9
4200	204200	208.2
4600	204600	224.4
5800	205800	281.5
7000	207000	336.1
9000	209000	444.4

SNAGA [W]	Tip MAPSV 30 W/m - 400 V	DUŽINA [m]
730	30730	24.4
850	30850	29.0
1230	301230	40.7
1900	301900	62.4
2200	302200	72.7
2800	302800	95.2
3700	303700	120.1
4400	304400	145.5
5100	305100	171.4
5600	305600	184.3
7000	307000	233.2
8500	308500	276.8
11000	3011000	363.6

